



## ACCESSORIES

- Set of 6 shaped separators 90mm kit.

Production by www.applebybowers.com 06/07 STARUK01

ELECTRICAL SERVICES	
Voltage	230 V
Current	15 Amp fused
Frequency	50 Hz
Maximum Consumption	1.3 kW
Refrigeration Capacity of Cooling Unit	750W



Presented by:

SPECIFICATION	
Height	1830mm
Depth	895mm
Depth (with door open)	1650mm
Width	850mm
Net Weight	348kg
No. of Drums	8 10
Drum Height	6 Drums at 130mm 10 Drums at 90mm 2 Drums at 90mm
Drum Diameter	700mm
No. of Compartments per drum	6 - 12 - 18 - 24 - 36
Max. Plate Size Vended	9 inch (230mm)
Max. Baguette Length Vended	260 - 270mm
Dispensing System	FIFO or Shopper
Rotation of Drum	Independent
Temp. Range - programmable default	2 - 19°C 3°C
Automatic Cut Out - default	2°C
Communication Protocol	Executive or BDV
Display	4 Line alphanumeric LCD
Price Bands	Programmable - one price per drum
Door Type	Automatic opening closing
Keypad	Direct selection pushbutton
Payment System	Compatible with all major coin and cashless systems using Executive and BDV protocol.

N&W reserve the right to alter the specification following any future enhancements made to this product.

# N&W

N&W GLOBAL VENDING LIMITED  
PO Box 25, Dudley Street, Bilston, West  
Midlands, WV14 0LF  
Tel: +44 (0) 1902 355000  
Fax: +44 (0) 1902 402272  
Web: [www.nwglobalvending.co.uk](http://www.nwglobalvending.co.uk)  
Email: [sales@nwglobalvending.co.uk](mailto:sales@nwglobalvending.co.uk)



automatic vending  
association



ISO 9001 : 2000



N&W GLOBAL VENDING S.P.A.  
Via Roma 24, 24030 Valbrembo (BG), Italy



ISO 9001 : 2000



ISO 14001




## features:

The Starfood offers the ideal solution to vending fresh food and snacks with simple loading, easy programming and flexibility. Appetising food is correctly preserved then dispensed hygienically. Should the set temperature deviate, the machine will not vend any products due to the safety cut out facility.

With a choice of either 8 or 10 drums, the Starfood can display a wide range of products from pre-packed sandwiches, fruit, yogurt and pastries to plated meals (9 inch diameter).

### TEMPERATURE

- Slide-in cooling unit
- Temperature control system blocks the machine if safety limit is not respected
- Cold air flows from central column outwards in each section, guaranteeing an even distribution of temperature.
- Double temperature: air flow is easily adjustable for each drum separately (Patent pending).

Contemporary looks enhanced by a back-lit photographic panel.

Simple direct selection push-button service with automatic sliders.

Two models available offering either 8 or 10 drums.

Up to 150 selections can be displayed at any time.

Compact yet the 700mm drum diameter allows a 9 inch plate to be vended.

Ideal for vending baguettes up to 270mm long using minimum space.

Complementary range of drink, snack and can vendors available.

The increased drum height of the 8 drum model is suited to the popular oversized triangular sandwich packs, which can be displayed correctly due to the higher than standard 130mm height. An innovative air flow system allows an even distribution of temperature or can be adjusted for each drum, to suit the products displayed - no more soggy pastries!

Prices are simple to set for each drum and are displayed electronically, which enhances the look of the machine as well as saving operator time.

The Starfood can be programmed to vend food using either the shopper mode or FIFO (first in first out) depending on the clients' requirements and is easy to use. Simply press the large vend button until the product you require is positioned in the slider zone, then press the selection button next to the slider zone and the slider will open automatically, allowing the product to be removed, then will close - couldn't be easier!

### PAYMENT SYSTEM

- Isolated compartment for payment system with separate access.
- Coin-mech, cashless and bill validator can be fitted onto the same machine.

Temperature Settings		Standard Drum Layout	
Standard	Optional	Starfood 10 drum	Starfood 8 drum
3°C	8°C-12°C	24	12
3°C		24	12
3°C		18	12
3°C		12	12
3°C		12	12
3°C		12	12
3°C	3°C	12	12
3°C	3°C	12	12
3°C	3°C	12	18
3°C	3°C	12	18
3°C	3°C		
3°C	3°C		
		Drum Height 90mm	Drum Height: Drums 1-6 = 130mm Drums 7&8 = 90mm
		Numbers shown indicate segments per drum	

The above diagram indicates the number of drums and the standard number of segments per drum. However, the standard layout can be changed very easily, by adjusting the separators to suit the products to be vended. Additional separators can be purchased as an accessory.